| L Number | Hits | Search Text | DB | Time stamp |
|----------|------|--|-----------|----------------------|
| 1 | 104 | trench adj isolation | IBM_TDB | 2003/12/17 14:55 |
| 2 | 28 | (trench adj isolation) same lining | EPO; JPO; | 2003/12/17 15:02 |
| | | | DERWENT | |
| 9 | 3 | ("5498565" "5578518" "5665635").PN. | USPAT | 2003/12/17 15:05 |
| 12 | 11 | ("4546538" "4631803" "4666556" "4719185" "4855804" | USPAT | 2003/12/17 15:06 |
| | | "4983226" "5183774" "5189501" "5206182" "5250829" | | |
| | | "5271972").PN. | | |
| 13 | 70 | 5447884.ÚRPN. | USPAT | 2003/12/17 15:07 |
| - | 573 | (257/324,326).CCLS. | USPAT; | 2003/12/17 14:12 |
| | | | US-PGPUB | |
| _ | 44 | ((257/324,326).CCLS.) and @pd>20030708 | USPAT; | 2003/12/17 14:14 |
| | | | US-PGPUB | |
| _ | 1 | ("6495853").PN. | USPAT: | 2003/12/17 14:15 |
| | | , | US-PGPUB | |
| - | 6 | ("6087696" "6093606" "6118147" "6177317" "6232635" | USPAT | 2003/12/17 14:14 |
| | | "6255689").PN. | | |
| _ | 9934 | trench adj isolation | USPAT: | 2003/12/17 14:15 |
| | | ······· | US-PGPUB | |
| _ | 75 | (trench adj isolation) same lining | USPAT: | 2003/12/17 15:02 |
| | | the state of the s | US-PGPUB | |
| _ | 9 | ("5231299" "5447884" "5597751" "5652161" "5851881" | USPAT | 2003/12/17 14:24 |
| | | "6017795" "6074927" "6093611" "6110800").PN. | | 2000, 12, 11, 11,2,1 |
| | 1 | 1 0011700 0071027 0000071 0710000 /.1 14. | l | 1 |

| | Document | Pages | Title | Current OR | Current XRef | Inventor |
|----|-----------------|-------|--|---------------|--|-------------------------|
| | US 6630390 B2 8 | - ω | Method of forming a semiconductor device using a carbon doped oxide layer to control the chemical mechanical polishing of a dielectric layer | 438/427 | 438/435; 438/637; 438/692 | Andideh, Ebrahim et al. |
| ~. | US 5926722 A | 80 | Planarization of shallow trench isolation by differential etchback and chemical mechanical polishing | 438/424 | 257/E21.244; 257/E21.246; 257/E21.251; 257/E21.546; 438/692; 438/734; 438/743; | Jang, S. M. et al. |
| | US 5786262 A | ō | Self-planarized gapfilling for shallow trench isolation | 438/424 | 148/DIG.50; 257/E21.279; 257/E21.546; 438/221; 438/296; 438/427; 438/435; | Jang, S. M. et al. |
| | US 5447884 A | 4 | Shallow trench isolation with thin nitride liner | 438/437 | 148/DIG.50; 257/E21.241; 257/E21.549; 438/702 | Fahey, Paul M. et al. |
| | US 4924284 A | ω | | 257/621 | 257/508; 257/513; 257/519; 257/520; 257/648; 257/E21.538; 257/E21.538; | Beyer, Klaus D. et al. |